

"MURRAY" GOLD SEAL CLAMPS








SAE TYPE "F"
1/2" Wide Worm Gear Clamps

"H" Series
With Zinc Plated Carbon Steel Screw
Band and housing are 201/301 stainless steel with 5/16" slotted hex head shouldered carbon screw, double plated with zinc plus Dichromate-Yellow. This economical clamp is the specified workhorse of the industry.

"H-SS" Series
With "400" Series Stainless Steel Screw
Band and housing are 201/301 stainless steel with 5/16" slotted hex head shouldered screw "400" Series Stainless Steel. The high corrosion of this all stainless steel band, housing and screw makes this the preferred clamp for numerous industrial installations.

Clamp Part No.		"A" Diameter Range					
Double Plated Screws	"400" Series Stainless Screws	Decimals		Millimeters		Inches	
		Min.	Max.	Min.	Max.	Min.	Max.
H 6	**H 6 SS**	.44	.78	11	20	7/16	25/32
H 8	**H 8 SS**	.44	.91	11	23	7/16	29/32
H 10	**H 10 SS**	.56	1.06	14	27	9/16	1-1/16
H 12	**H 12 SS**	.69	1.25	18	32	11/16	1-1/4
H 16	**H 16 SS**	.75	1.50	19	38	3/4	1-1/2
H 20	**H 20 SS**	.81	1.75	21	44	13/16	1-3/4
H 24	**H 24 SS**	1.06	2.00	27	51	1-1/16	2
H 28	**H 28 SS**	1.31	2.25	33	57	1-5/16	2-1/4
H 32	**H 32 SS**	1.56	2.50	40	64	1-9/16	2-1/2
H 36	**H 36 SS**	1.81	2.75	46	70	1-13/16	2-3/4
H 40	**H 40 SS**	2.06	3.00	52	76	2-1/16	3
H 44	**H 44 SS**	2.31	3.25	59	83	2-5/16	3-1/4
H 48	**H 48 SS**	2.56	3.50	65	89	2-9/16	3-1/2
H 52	**H 52 SS**	2.81	3.75	71	95	2-13/16	3-3/4
H 56	**H 56 SS**	3.06	4.00	78	102	3-1/16	4
H 60	**H 60 SS**	3.31	4.25	84	108	3-5/16	4-1/4
H 64	**H 64 SS**	3.56	4.50	90	114	3-9/16	4-1/2
H 72	**H 72 SS**	4.06	5.00	103	127	4-1/16	5
H 80	**H 80 SS**	4.56	5.50	116	140	4-9/16	5-1/2
H 88	**H 88 SS**	5.06	6.00	129	152	5-1/16	6
H 96	**H 96 SS**	5.56	6.50	141	165	5-9/16	6-1/2
H 104	**H 104 SS**	6.06	7.00	154	178	6-1/16	7
H 116	**H 116 SS**	6.50	7.75	173	197	6-1/2	7-3/4
H 128	**H 128 SS**	5.69	8.50	144	216	5-11/16	8-1/2
H 140	**H 140 SS**	6.44	9.25	163	235	6-7/16	9-1/4
H 152	**H 152 SS**	7.19	10.00	182	254	7-3/16	10
H 164	**H 164 SS**	7.94	10.75	201	273	7-15/16	10-3/4
H 176	**H 176 SS**	8.69	11.50	225	292	8-11/16	11-1/2
H 188	**H 188 SS**	9.44	12.25	239	311	9-7/16	12-1/4
H 200	**H 200 SS**	10.19	13.00	259	330	10-3/16	13
H 212	**H 212 SS**	10.94	13.75	277	349	10-15/16	13-3/4
H 224	**H 224 SS**	11.69	14.50	296	368	11-11/16	14-1/2
H 236	**H 236 SS**	12.44	15.25	315	387	12-7/16	15-1/4
H 248	**H 248 SS**	13.19	16.00	335	406	13-3/16	16

BANDIMEX UNIVERSAL HOSE AND PIPE CLAMPS



Using the BANDIMEX tool, a roll of BANDIMEX band and BANDIMEX buckles, a clamp fitting each diameter and each shape can easily and quickly be applied at low cost, to clamp all types of hose, fix signs and boards to

BANDIMEX TOOL

W 001 Tool, tensioning



BANDIMEX BAND full round edge, 30 m/roll

SS-CrNi	SS-CrNiMo	width	thickness	kg
B 202	B 402	6.4 mm - 1/4”	0.50 mm - .020”	0.8
B 203	B 403	9.5 mm - 3/8”	0.64 mm - .025”	1.5
B 204	B 404	12.7 mm - 1/2”	0.75 mm - .030”	2.3
B 205	B 405	16.0 mm - 5/8”	0.75 mm - .030”	2.9
B 206	B 406	19.0 mm - 3/4”	0.75 mm - .030”	3.4



BANDIMEX BUCKLES for single or double wrapped BANDIMEX band, 100/box

SS-CrNi	SS-CrNiMo	for band width	kg
S 252	S 452	6.4 mm - 1/4”	0.1
S 253	S 453	9.5 mm - 3/8”	0.4
S 254	S 454	12.7 mm - 1/2”	1.0
S 255	S 455	16.0 mm - 5/8”	1.1
S 256	S 456	19.0 mm - 3/4”	1.7



BANDIMEX SCRU-BUCKLES for retensioning clamps - easily applied, SS

	for band width	quantity	kg
S 720	6.4 mm - 1/4”	50	0.1
S 722	9.5 mm - 3/8”	50	0.2
S 724	12.7 mm - 1/2”	25	0.2
S 726	189.0 mm - 3/4”	25	0.4



BANDIMEX L-BAND for light duty jobs, SS, 0.4 mm - .016” thick - round edge

Width	90m	kg	60m	kg	30m	kg
9.5 mm - 3/8”	B 123	2.7	B 127	1.8	B 133	0.9
12.7 mm - 1/2”	B 124	3.7	B 128	2.4	B 134	1.2
16.0 mm - 5/8”	B 125	4.6	B 129	3.1	B 135	1.5
19.0 mm - 3/4”	B 126	5.5	B 130	3.6	B 136	1.8



BANDIMEX L-BAND PLUS 0.5 mm. - .020” - round edge

12.7 mm - 1/2”	-		B 183	3.0	B 181	1.5
19.0 mm - 3/4”	-		B 163	4.6	B 161	2.3

BANDIMEX L-CLIPS - for use with L-Band,m SS, reinforcing ribs, 100/box

	for band width	kg
S 153	9.5 mm - 3/8”	0.3

