



SAE 100 R6 / EN 854

Temperature Range	: -40°C (-40°F) to +120°C (+248°F)
Application	: Low Pressure Hydraulic Oils, Air And Water
Tube	: Synthetic Oil Resistant Rubber
Reinforcement	: 1 Textile Braids
Cover	: Synthetic Rubber - Abrasion, Ozone And Weather Resistant
Branding	: Inkjet White 'SUNFLEX SAE 100 R6 / EN 854'

Hose Size					Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Hose Weight
Part Number	Dash	I.D.		O.D.							
		inch	mm	mm	psi	bar	psi	bar	inch	mm	m/kg
R6-04	-4	1/4	6.4	12.7	400	28	1600	110	2.5	64	0.105
R6-05	-5	5/16	7.9	14.3	400	28	1600	110	3.0	76	0.125
R6-06	-6	3/8	9.5	15.9	400	28	1600	110	3.0	76	0.150
R6-08	-8	1/2	12.7	19.8	400	28	1600	110	4.0	102	0.200
R6-10	-10	5/8	15.9	23.0	350	24	1400	97	5.0	127	0.255
R6-12	-12	3/4	19.0	26.0	300	21	1200	83	6.0	152	0.305
R6-16	-16	1	25.4	32.5	190	13	760	52	9.1	230	0.455