



AHT220 ASPHALT HOSE 200 PSI

A Strong Yet Flexible Hose, Specially Designed As Tank Truck Or Tank Wagon Hose For Loading And Unloading Hot Asphalt.

- Temperature Range** : -15°C (-5°F) to +185°C (+365°F)
- Tube** : Black, Smooth, Polyacrylic Compound
- Reinforcement** : Plies Of Steel Wire Cord Plus Helix Wire
- Cover** : Black, Smooth (Wrapped Finish) Special Synthetic Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion, Tar And Oil
- Coils** : Size 3/4" to 5" Supply In 61mt (200ft) Continuous Length
- Branding** : White Transfer Tape With Negative Text
'SUNFLEX AHT 220 ASPHALT HOSE WPSI 220'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
AHT220-0150	38.0	1-1/2	56	2-13/64	15	220	45	660	228	1.87	1.26
AHT220-0200	50.8	2	71	2-51/64	15	220	45	660	305	2.83	1.90
AHT220-0250	63.5	2-1/2	81	3-3/16	15	220	45	660	381	3.00	2.01
AHT220-0300	76.2	3	94	3-45/64	15	220	45	660	457	3.56	2.40
AHT220-0350	90.0	3-1/2	112	4-13/32	15	220	45	660	540	5.05	3.40
AHT220-0400	101.6	4	126	4-31/32	15	220	45	660	610	6.19	4.16
AHT220-0500	127.0	5	155	6-7/64	15	220	45	660	762	9.02	6.06
AHT220-0600	152.4	6	184	7-1/4	15	220	45	660	914	12.43	8.35